




V1	V5 ECC83/7025	120V	-70V*	0	30V	-70V*	0
V2	V6 ECC82/12AU7	190V	+	0	205V	+	0
V3	V7 ECC83/12AX7	195V	0	12V	300V	165V*	18.5V
V4	V8 ECC83/12AX7	-30V*	-30V*	+	170V	0	0

* MEASURED WITH A V.T.V.M.
* MEASUREMENTS UNRELIABLE AS EVEN A V.T.V.M. WILL LOAD CIRCUIT AND VOLTAGES WILL VARY WITH SIGNAL LEVEL.

Resistor ratings are 1/2 watt and resistance values are ± 10 otherwise noted.
D.C. voltages are measured to ground with a 20,000 ohms per meter, no signal input.
Signal voltages are encircled (007) and measured to ground A.C. V.T.V.M.
The signal frequency must be 1 kc with volume control at max frequency range switch at full and fidelity equalizer set at 1



* MEASURED WITH A V.T.V.M.
* MEASUREMENTS UNRELIABLE AS EVEN A V.T.V.M. WILL LOAD CIRCUIT AND VOLTAGES WILL VARY WITH SIGNAL LEVEL.

D.C. VOLTAGE READINGS									
	V1	V2	V3	V4	V5	V6	V7	V8	V9
V1	ECC83/7025	110V	-55V*	0	115V	-55V*	0		
V2	ECC82/12AU7	150V	+	0	150V	+	0		
V3	ECC83/12AX7	225V	0	19V	300V	165V	19.5V		
V4	ECC83/12AX7	-30V*	-30V*	+	190V	0	1.0V		

NOTE:
Capacitor ratings are 500V min. unless otherwise noted.
Resistor ratings are 1/2 watt and resistance values are $\pm 10\%$ unless otherwise noted.
D.C. voltages are measured to ground with 20,000 ohms per volt meter no signal input.
Signal voltages are encircled (010) and measured to ground with an A.C. V.T.V.M. The signal frequency must be 1 K.C. with volume control at max., high frequency range switch at full and fidelity equalizer set at 1.

