

Socket: CRT-10-Stift-socket 5&5 Allglas

Base: CRT 10-pin (5 & 5) all glass

Country: Grossbritannien

Pins: 10

Pin Diameter: 1,3 mm

Pin Circle: 28 mm

Tube: CRT:

Pin length: 8 mm

Spigot: ingen

Comments: Tout en verre, avec deux broches plus petites.



Base: Noval+1 (10= center pin) = B10G = E10-73

Pin Diameter: 1,0 mm

Circle: 11,9 mm Pin

Tubes : 6C9, 6J9,8843, 8894, 17C9, 19Q9



Socket: Dekal (ähnl. Noval, aber 10-Stift)

Base: Dekal, B10C

Names: B10B, decal

Country: Niederlande

Year: 1964

Pins: 10

Pin Diameter: 1 mm

Pin Circle: 11,9 mm

First Tube: ECH200, PFL200

Pin length: 7,1 mm max



Socket: TFK-10-Stift G10G

Base: TFK-10-pin G10G

Country: Deutschland

Pins: 10

Pin Diameter: 2,5 mm og 1,4 mm (1 tykk og 9 tynne)

Tube: EL152, EL153, FL152

Names: G10G

Pin length: 8 mm



Socket: Stahlröhrensocket 5/5-Stifte, Y10A

Base: German Steel 10 pin, Y10A

Tube: oscillo

