

Subminiature Fuses w/Axial & Radial Leads



GFA

Axial Leads, Fast Acting

Physical Size:

0.145" × 0.300"
(3.7mm × 7.6mm)

Construction: Glass Tube

Interrupting Rating: 50 AIC

Agency Approvals:

UL Recognized, Guide JDYX2,
File E19180, 0-5A
CSA Certified, Class 1422-01,
File 53787, 0-5A

Catalog Symbol & Current Ratings

Amps	Test Spec.	Color Code (Opposite Ends)	
125 VAC			
GFA-1/200	A	Red	Blk
GFA-1/100	A	Red	Orn
GFA-1/64	A	Red	Grn
GFA-1/50	A	Red	Wht
GFA-1/32	A	Red	Brn
GFA-1/20	A	Yel	Yel
GFA-1/16	A	Brn	Brn
GFA-1/10	A	Red	Red
GFA-1/8	A	Orn	Orn
GFA-15/100	B	Red	Yel
GFA-2/10	B	Red	Blu
GFA-1/4	B	Red	Pur
GFA-3/10	A	Grn	Grn
GFA-1/10	A	Blu	Blu
GFA-1/2	B	Orn	Grn
GFA-9/10	B	Orn	Blu
GFA-3/4	B	Orn	Pur
GFA-1	B	Yel	Grn
GFA-1 1/2	B	Yel	Pur
GFA-2	B	Grn	Blu
GFA-2 1/2	B	Grn	Brn
GFA-3	B	Blu	Pur
GFA-4	B	Pur	Brn
GFA-5	B	Brn	Blk
32 VAC			
GFA-7	A	Pur	Grn
GFA-8	A	Grn	Blk
GFA-10	A	Yel	Brn
GFA-12	A	Blk	Blu
GFA-15	A	Blk	Pur



GLN

Radial Leads, Fast Acting

Physical Size:

0.145" × 0.300"
(3.7mm × 7.6mm)

Construction: Glass Tube

Interrupting Rating: 50 AIC

Catalog Symbol & Current Ratings

Amps	Color Code (Opposite Ends)	
125 VAC		
GLN-1/100	Red	Orn
GLN-1/32	Red	Brn
GLN-1/20	Yel	Yel
GLN-1/16	Brn	Brn
GLN-1/10	Red	Red
GLN-3/10	Grn	Grn
GLN-1/10	Blu	Blu
32 VAC		
GLN-7	Pur	Grn
GLN-8	Grn	Blk
GLN-10	Yel	Brn



GLX

Radial Leads, Fast Acting

Physical Size:

0.145" × 0.300"
(3.7mm × 7.6mm)

Construction: Glass Tube

Interrupting Rating: 50 AIC

Catalog Symbol & Current Ratings

Amps	Color Code (Opposite Ends)	
125 VAC		
GLX-1/4	Red	Pur
GLX-1/2	Orn	Grn
GLX-3/4	Orn	Pur
GLX-1	Yel	Grn
GLX-1 1/2	Yel	Pur
GLX-2	Grn	Blu
GLX-3	Blu	Pur
GLX-4	Pur	Brn
GLX-5	Brn	Blk

